



1	SHCS, DRILLED (TORQUE TO 50 IN. LBS.)	10-24X1.75SHCS(A)	2	9A	BRASS RIVET	4-4	2				
2	BOLT	AN3-20A	2	10	PISTON 4" BRAKE	PI-2	1				
3	WASHER	AN960-10L	4	11	O-RING BUNA N	2-218	1	19	BRAKE DISC, 4" BRAKE	D4	1
3A	WASHER	AN960-10	2	12	PUCK HOUSING, 4" BRK	PH-2	1				
4	STATIONARY BRAKE SHOE, 4"/UL	SBS4	1					20	SHCS, DRILLED (TORQUE 40 IN. LBS.)	10-24X.75SHCS(A)	3
5	LINING, 4"/UL	M66-103A	2	13	FLEX LOCK NUT, .25-28 (TORQUE 50 IN. LBS.)	MS21045-3	3	21	BOLT	AN3-20A	3
6	BRASS RIVET	4-6	2	14	WASHER	AN960-10L	6	22	DUST PLUG	.234-.50IL	1
7	SPACER, 4"/UL	BSP4	4	15	BEARING	LM11900LA	2	23	BRAKE BLEEDER VALVE	F6446-007	1
8	BRAKE PLATE, .75	BPA.75MH	1	16	BEARING RACE	LM11910	2	24	BRAKE BLEEDER SEAT	BBS(A)	1
9	MOVEABLE BRAKE SHOE, 4"/UL	MBS4	1	17	VALVE HALF, 4" WHL, .75 BRNG	W40/.75	1				
				18	BRAKE HALF, 4" WHL, .75 BRNG	B40/.75	1	25	LOCK NUT (TORQUE TO 50 IN. LBS.)	10-24NYLOCK	2
								26	CAPLUG	2X	1
NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D

TD-WH40  
**MATCO mfg.**  
 2361 S 1560 West  
 WOODS CROSS, UT 84087 (801) 335-0582

**W 4 O R**

DRAWN BY: GARY P. LANGFORD  
 AUTHORIZED BY:

SCALE: NONE  
 DATE: FEBRUARY 9, 1993

REVISION:  
 A