



1	SHCS, DRILLED (TORQUE TO 50 IN. LBS.)	10-24X1.75SHCS(A)	2	9A	BRASS RIVET	4-6	2	19	BRAKE DISC, 4" BRAKE	D4	1
2	SHCS	10-24X1.75SHCS	2	10	ROLLER BEARING, .75	LN11B00LA	2	20	SHCS, DRILLED (TORQUE 40 IN. LBS.)	.10-24X.75HCS(A)	3
3	WASHER	AN960-10L	6	11	PISTON 4" BRAKE	PI-2	1	21	BOLT	A4-15A	3
4	STATIONARY BRAKE SHOE, 4"/UL	SBS4	1	12	O-RING BUNA N	2-21B	1	22	DUST PLUG	.234-.50IL	1
5	LINING, 4"/UL	M88-103A	2	13	FLUCK HOUSING, 4" BRAKE	PH-2	1	23	BRAKE BLEEDER VALVE	F8446-007	1
6	BRASS RIVET	4-6	2	14	FLEX LOCK NUT .25-28 (TORQUE 50 IN. LBS.)	AN363-42B	3	24	BRAKE BLEEDER SEAT	BBS(A)	1
7	SPACER, 4"/UL	BSP4	4	15	WASHER	AN960-416L	6	25	LOCK NUT (TORQUE TO 50 IN. LBS.)	10-24NYLOC	2
8	BRAKE PLATE, .75 BD	BPA.75BD	1	16	BEARING RACE, .75	LN11910	2	26	CAPPLUG	2X	1
9	MOVEABLE BRAKE SHOE, 4"/UL	MBS4	1	17	VALVE HALF, 4" WHL, .75 BRNG	W40BD/.75	1				
				18	BRAKE HALF, 4" WHL, .75 BRNG	B40BD/.75	1				
NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D

3D-WH40

**DATE** mfg  
550W 3815 South  
SALT LAKE CITY, UT 84115 (801) 486-7574

W40BD

DRAWN BY: GARY P. LANGFORD  
AUTHORIZED BY:

SCALE: NONE  
DATE: MARCH 4, 1993

REVISION:  
A