



1	BOLT, DRILLED (TORQUE TO 50 IN. LBS.)	.25-20X2BOLT(A)	4									
2	BOLT	AN4-20A	4	12	ROLLER BEARING, 1.25	LM6700LA	2					
3	WASHER	AN960-416L	14	13	FLEX LOCK NUT, .25-28 (TORQUE TO 50 IN. LBS.)	AN363-428	3					
4	STATIONARY BRK SHOE, 5/6"	SBS5	2					19A	WASHER	AN960-416	4	
5	LINING, 5/6" BRAKE	M66-106	4	14	BEARING RACE, 1.25	LM67010	2	20	BRAKE PLATE, DUAL	BPD1.38	1	
6	BRASS RIVET	4-6	12	15	VALVE HALF, W50, 1.25 BRNG	W50/1.25	1	21	DUST PLUG	.234-.50IL	2	
7	SPACER, DUAL/TRIPLE PUCK	BSP6	8	16	BRAKE HALF, W50L, 1.25 BRNG	B50L/1.25	1	22	BRAKE BLEEDER VALVE	F6446-007	2	
8	MOVEABLE BRK SHOE, 5/6"	MBS5	2	17	BRAKE DISC, 5/6"	D5D	1	23	BRAKE BLEEDER SEAT	BBS(A)	2	
9	PISTON, 5/6" BRAKE	PI-1	2	18	SHCS, DRILLED (TORQUE TO 40 IN. LBS.)	.25-20X.75SHCS(A)	3	24	LOCK NUT (TORQUE TO 50 IN. LBS.)	.25-28NYLOC	4	
10	O-RING BUNA N	2-222	2	19	BOLT	AN4-22A	3	25	PUCK HOUSING, 5/6" BRAKE	PH-1	2	
11	CAPLUG	2X	2									
NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D	NO.	PART NAME	INVENTORY NO.	REQ'D	

3W50S75A
 MATCO mfg
 2361 S 1560 West
 WOODS CROSS, UT 84087 (801) 335-0582

W 5 0 L D

DRAWN BY: GARY P. LANGFORD
 CHECKED BY:

SCALE: NONE
 DATE: OCTOBER 4, 1991

REVISION:
 A